


型号: KH-IPEX3-SMA-RG081-80mm

REVISIONS					
REV	NUMBER	DESCRIPTION	DWN	CHK	DATE
A		DESIGN			



三個配件出貨時另外附配件出貨(墊片,華司,螺母)

NOTES:

- ELECTRICAL:
 - VOLTAGE RATING:DCV 300V 10MS
 - CONDUCTANCE RESISTANCE:3.0 OHMMAX.
 - INSULATION RESISTANCE:5.0M OHMMIN.
 - THE CABLE SHOULD BE 100% ELECTRICAL TEST
 - IT SHOULD BE NO ANY OPEN/SHORT, MISWIRING AND INTERMITTENT FAILURES.
- MATERIAL:
 - SEE TABLE
 - ALL COMPONENTS ARE ROHS COMPLIANT.

ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
④	套管	黑色热缩套管, OD:2.0MM	AS
③	端子	高仿IPEX 0.81 3代端子, 镀金	1
②	接头	SMA母头母针, 分体, 11牙, 镀金	1
①	同轴线	RF 0.81线材,颜色: 黑色, OD:0.81mm	AS

金航标电子有限公司

ALL DIMENSION ARE IN MM	DRAWN	DATE
	Janny	2020-06-18

COMPUTER GENERATED IN SOLIDWORKS	MFG.
DO NOT SCALE THIS DRAWING	Q.A.


PROJECTION	GENERAL TOLERANCE FOR ANGLES
	X.X X.XX X.XXX
	± 1° ± 0.3 ± 0.25 ± 0.150

CUSTOMER P.N.:

I-PEX 0.81 3代 TO SMA /F L= 80 mm

SIZE	Number	REV
B		A

SCALE: Free	TYPE	SHEET 1 OF 1
-------------	------	--------------



技术详询

A

B

C

D

4

3

2

1

A

B

C

D

4

3

2

1